



## Technical Data Sheet. Tribond 1194

**Chemical Nature**  
**Solids**  
**Viscosity.**  
**pH**  
**Specific Gravity.**

**Synthetic co-polymer**  
**Approx. 48 %**  
**Approx. 400 cps**  
**4.0-6.0**  
**Approx 1.05**

### DESCRIPTION.

Tribond 1194 is a fast setting, low viscosity, jetting adhesive for carton side seams. Designed to be run through fine nozzles at high speeds, Tribond 1194 is suitable for use on most carton boards, with the exception of film laminated or film coated products, including grease resistant boards.

Tribond 1194 has been formulated to give excellent high temperature and creep resistance. The components of Tribond 1194 meet the requirements of FDA 21CFR 175.105, for indirect food contact.

Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

### STORAGE.

Store at temperature above 7°C to prevent damage by frost.  
The storage life of this product is 3 months from date of manufacture.

### HEALTH AND SAFETY.

None hazardous  
Refer to the Material Safety Data Sheet for more information.

### CAUTION.

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.