



Technical Data Sheet Tribond 1016

Chemical Nature

Solids
Viscosity.
pH
Specific Gravity.

Copolymer Emulsion

Approx.55 %
Approx. 2400 cps
4.5-5.5
Approx. 1.04

DESCRIPTION

Tribond 1016 has been specially developed as a versatile adhesive for bonding box and carton board, wood and foam products. Tribond 1016 has excellent wet tack properties and is very fast drying. Application can be by hand/bottle or traditional coating methods. Once dried laminates show excellent creep resistance and can withstand high service temperatures. This product has been found to be suitable for producing oven and microwave resistant laminates.

Tribond 1016 has good binding and wetting properties for padding applications (including ncr) and bonding foam to board.

The ingredients of Tribond 1016 have food contact approval according to FDA 175.105, 176.170, 176.180.

Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

STORAGE

Store at temperature above 7°C to prevent damage by frost.
The storage life of this product is 3 months from date of manufacture.

HEALTH AND SAFETY

None hazardous
Refer to the Material Safety Data Sheet for more information.

CAUTION

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.