



Technical Data Sheet. Tribond 1238

Chemical Nature
Solids
Viscosity.
pH
Specific Gravity.
Tg

Acrylic Emulsion
Approx.58 %
Approx. 1000 cps
4.5-5.5
Approx. 1.05
-34°C

DESCRIPTION.

Tribond 1238 has been specially developed as permanent, general purpose adhesive for the packaging industry. Tribond 1238 has excellent adhesion to many substrates including Polyethylene, Polypropylene, PVC, Polyester, paper, board and many fabrics. Tribond 1238 has aggressive tack at low and high temperatures making it suitable for use in freezer to oven food packaging. Tribond 1238 dries to form a tacky film which exhibits a good balance of tack and shear strength.

The ingredients of Tribond 1238 comply with FDA 175.105, 176.170, 176.180 and BGA XIV. Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

STORAGE.

Store at temperature above 7°C to prevent damage by frost.
The storage life of this product is 3 months from date of manufacture.

HEALTH AND SAFETY.

None hazardous
Refer to the Material Safety Data Sheet for more information.

CAUTION.

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.