



## Technical Data Sheet. Tribond 1224

**Chemical Nature**  
**Solids**  
**Viscosity.**  
**pH**  
**Specific Gravity.**

**Copolymer Emulsion**  
**Approx. 69 %**  
**Approx. 1000 cps**  
**6.0-8.0**  
**Approx. 1.04**

### DESCRIPTION

Tribond 1224 has been developed as a long open time, laminating adhesive for porous substrates used in the graphic arts industry. Tribond 1224 offers excellent machining properties, easy cleaning and good adhesion to a wide range of substrates. Tribond 1224 is a neutral pH adhesive, which uses ingredients that conform to F&DA 21 CFR 175.105. The product is also re-dispersible.

Tribond 1224 can also be used as a repositionable mounting adhesive.

For best adhesion results the surface energy of the substrate should be a minimum 40d/cm. Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

### STORAGE.

Store at temperature above 7°C to prevent damage by frost.

The storage life of this product is 3 months from date of manufacture.

### HEALTH AND SAFETY.

None hazardous

Refer to the Material Safety Data Sheet for more information.

### CAUTION.

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.