



Technical Data Sheet. Tricote 1260

Chemical Nature
Solids
Viscosity.
pH
Specific Gravity.

PolyDimethylSiloxane
Approx. 13 %
n/a
n/a
Approx. 1.00

DESCRIPTION

Tricote 1260 is an aqueous defoamer for water based products. Addition levels from 0.1%-0.5% have shown best results. Tricote 1260 can be mixed with a variety of polymer systems; typically natural rubber latex based products. Care should be taken to avoid over dosing as this can have a detrimental effect on surface coatings.

All the components are approved in 21CFR 176.210 with exception of two minor components which account 0.4% of the formulation.

The minor components are approved as components of food contact paper under 21CFR 176.170 and 21CFR 175.105 FDA regulations.

Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

STORAGE.

Store at temperature above 7°C to prevent damage by frost.

The storage life of this product is 3 months from date of manufacture.

HEALTH AND SAFETY.

None hazardous

Refer to the Material Safety Data Sheet for more information.

CAUTION.

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.