



## Technical Data Sheet Tricote 1213

**Chemical Nature**  
**Solids**  
**Viscosity.**  
**pH**  
**Specific Gravity.**

**Inkjet printable coating**  
**Approx. 15 %**  
**Approx. 500 cps**  
**6.0 – 7.0**  
**Approx. 1.05**

### DESCRIPTION

Tricote 1213 is a water-based, matt, inkjet printable coating for paper and treated films. Developed for simple papers and security labels, Tricote 1213 offers fast drying times and has been used on MEMJET printing machines. The dried film is highly sensitive to water and is easily removed from filmic substrates with sellotape.

For best adhesion results the surface energy of the substrate should be a minimum 40d/cm. Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

### STORAGE

Store at temperature above 7°C to prevent damage by frost.  
The storage life of this product is 3 months from date of manufacture.  
Mix before use.

### HEALTH AND SAFETY

None hazardous  
Refer to the Material Safety Data Sheet for more information.

### CAUTION

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.