



## Technical Data Sheet Tribond 1274

**Chemical Nature**  
**Solids**  
**Viscosity.**  
**pH**  
**Specific Gravity.**

**SBR Latex**  
**Approx. 52 %**  
**Approx. 500 cps**  
**7.0 – 8.0**  
**Approx. 1.04**

### DESCRIPTION

Tribond 1274 is a premium grade SBR with very high water resistance, excellent binding properties and very good mechanical stability.

Tribond 1274 is typically used in the building trade to formulate liquid applied damp proofing compounds, as an admixture for renders and screeds or in repair compounds.

Tribond 1274 has the following benefits;

- Improves adhesion
- Excellent in damp conditions
- Improves strength and workability of mixes
- Improves flexibility and reduces cracking
- Improves water and chemical resistance

For specific recommendations on mix volumes, please see our Tribond 1274 user guide.

Users should evaluate the product to make sure all requirements are satisfied before going in to full production.

### STORAGE

Store at temperature above 5°C to prevent damage by frost, but below 25°C to avoid degradation.

The storage life of this product is 6 months from date of manufacture.

### HEALTH AND SAFETY

None hazardous according to EC directive 1999/45/EC

Refer to the Material Safety Data Sheet for more information.

### CAUTION

This product has been manufactured to current quality and production specifications. Users of this product must carry out their own trials to ensure all requirements are satisfied. Trillium cannot guarantee the products suitability for the specific purpose of the customer due to the many factors that may affect storage, processing and application.